


MAUSER

S P E Z I A L

MA 1245

Single and two-needle lockstitch flat bed sewing machines with unison feed



Area of application:

Sewing of medium-heavy materials, e.g. furniture and car upholstery, leather clothing, leather goods, etc.

Special features:

- High traction due to unison feet.
- Even feed motion without any ply-shift of individual layers.
- Large vertical rotary hook with 60% more bobbin thread capacity than other standard-sized hooks. ■ Automatic hook lubrication.
- Efficient hook protection against thread jamming due to standard built-in overload coupling (M).
- Rugged and durable.
- The high top feed lift (7 mm) allows trouble-free sewing of thick materials and an easy sewing over cross seams.
- Easy to service.
- Easy loading and unloading – even of bulky material – due to a high fabric clearance of 14 mm

Explanations and additional equipment:

- **-6/07 CN** Special part set for seams with particularly bulky cross seams stitch length max 6 mm, available for machines with thread trimmer -900/56 and for machines without thread trimmer.
- **-6/07 CN8** Same as -6/07 CN, but stitch length 8 mm
- **-17/01-650/03 CN** Part set for binding, without binder (for machines without P)
- **-40/01 CN x 5.0** Piping part set for piping size 5 mm, device for the manufacture and simultaneous insertion of piping between two plies of fabric, device fastened on retractable carrier.

MAUSER

S P E Z I A L

Standard Supply Program:	Hook protection device (M)	Four-motion-drop-feed feed (P)	Thread trimmer - 900/56	Automatic presser-foot lifter / backtacking system -911/97	Stitch length in mm
1245-6/01 CLPMN	●	●			6
1245-6/01 CLPMN8	●	●			8
1245-6/01 CLMN8	●				8
1245-6/01-900/56 CLPMN	●	●	●		6
1245-6/01-900/56 CLPMN8	●	●	●		8
1245-6/01-900/56-911/97 CLPMN*	●	●	●	●	6

*An air filter/pressure regulator -925/03 is required for the operation of all machines with -911/97.

- C for sewing medium-heavy to heavy materials
- L leather
- S fabric
- P four-motion-drop-feed



MAUSER

S P E Z I A L

Technical **Data:**

Stitch type:
301 (lockstitch)

Max speed:**
2800

Top feed lift:
7 mm

Fabric clearance:
max. 14 mm

Needle system:
134-35

Needle size: 110-
140 Nm

Balance wheel:

80 mm eff. dia

Motor power:

0.370 or 0.550 kW,
depending on equipment

Clear work space:

270 x 115 mm

Carton dimensions:

77 x 62 x 38 cm

Bedplate dimensions:

476 x 177 mm

Net weight of head:

approx. 36 kg

**Gross weight (head in carton w/
accessories):**

approx. 44 kg

This machine is equipped with finger-guard, belt- and take-up lever guards as standard.

** = depending on setting of top feed lift, material and production process.



Collier Equipment

100 Mill Creek Circle / PO Box 175

Lexington, AL 35648

Ph: (256) 229-6595 Fx: (256) 229-6779

CollierEquipment.com